



RoHS HF REACH




CONNECTION DIAGRAM



SEQUENCE OF EXCITATION

		SEQUENCE OF EXCITATION			
PHASE \ STEP		1	2	3	4
A		H	H	L	L
$\bar{A}$		L	L	H	H
B		L	H	H	L
$\bar{B}$		H	L	L	H

PIN	NOTOR TERMINAL	CABLE WIRE COLOUR
1	A	WHITE
2	A	BLACK
3	B	BLUE
4	B	RED



1.1" F2.4/35MM /20MEGA/C MOUNT		WORKING DISTANCE	OPTICAL MAGNIFICATION	1.1" FIELD OF VIEW		ELECTRICAL CHARACTERISTIC	
FOCAL LENGTH	f=35MM	MM		H	V	Rated Voltage(额定电压):	5.0V DC Constant
F. NO	F=1:2.4--16	5000	0.007X	2079.07	1559.30	Operating Voltage Range(使用电压范围):	3.3V~5.0V
FOCUS DISTANCE	0.1M	2000	0.017X	824.332	618.249	Excitation Method(激励方式):	2 Phase Excitation
FLANGE BACK	17.526MM IN AIR	1000	0.035X	406.235	304.676	Coil Resistance(线圈电阻):	19Ω ± 10%
BACK FOCUS	22.2	900	0.039X	364.451	273.338	Step Angle(步进角度):	0.12° Step(ref)
FILTER SCREW SIZE	M35.5*P0.5	800	0.044X	322.678	242.009	Withstand Voltage(耐压):	AC 100 V/3mA
MOUNT	C	700	0.05X	280.924	210.693	Insulation Resistance(绝缘阻抗):	10M Ω(AT500pps 5v DC)
REL. ILLUMINATION	≥70%	600	0.059X	239.197	179.398	Mechanical Specication(机械特性):	
Front/Rear Effective Dia	Front Ø21.5 Rear Ø17.2	500	0.071X	197.519	148.139	Final Transmission Ratio(减建比):	20:1
FIELD OF VIEW	SENSOR	1.1"	1"	2/3"		Gear Box3 Output Torque(输出扭矩):	450gf·cm(min)(AT 500pps, 5v DC)
	D	26.3°	24.4°	16.9°		Max.Slew rate(最大连续响应频率):	2500pps/min(AT 5 v DC)
	H	21.5°	19.6°	13.6°		Max.Start rate(最大启动频率):	1000pps/min(AT 5 v DC)
	V	16.3°	14.8°	10.2°		Mechanical Noise(机械噪音):	60dB (max)DC 5v 500pps
TV DISTORTION	<0.1% <0.05% <0.05%	300	0.104X	135.193	101.395	齿轮出力参数:	
外观标准	60--40	250	0.123X	114.527	85.896	齿轮齿形:	JIS B 1701: 分度圆直径: φ6.4/φ48.4
WORKING TEPMERATRUE	-40℃~80℃	200	0.150X	93.978	70.483	模数:	0.4 齿顶圆直径: φ7.2/φ49.2
STORAGE TEPMERATRUE	-40℃~85℃	150	0.191X	73.636	55.227	压力角:	20° 齿根圆直径: φ5.4/φ47.4
		100	0.262X	53.887	40.415	齿数:	16 / 121 精度: JGMA-116-02 5级
Common Tolerance	④					Material:	
Angle	±0.5°	③				#	
0.000	±0.01	②				3RD ANGLE PROJN	
0.00	±0.03	①				Model:	
0.0	±0.05	Rev	Description	Name	Date	1.1"-35mm-20M	
0	±0.1	Design	Examine	Checked	Approved	Part Name:	
					CHKP	DFA3512D规格书	
						Dwg No:	
						DFA3512D-SPEC-V0	