

RoHS HF REACH

(31.8-37.8)

紧固螺丝 紧固螺丝

像面

35MM /C MOUNT

FOCAL LENGTH	f=35MM
F. NO	2.2~16
FOCUS DISTANCE	0.1M---INF
FLANGE BACK	17.526MM IN AIR
BACK FOCUS	17.4
FILTER SCREW SIZE	M25.5*P0.5
MOUNT	C
REL. ILLUMINATION	≥75%
Front/Rear Effective Dia	Front Ø16.2 Rear Ø8.6


FIELD OF VIEW	SENSOR	2/3"	1/2.5"	1/3"
	D	16.3°	10.9°	8.7°
	H	13.2°	8.6°	6.9°
	V	9.9°	6.3°	5.2°

TV DISTORTION		<0.1%	<0.1%	<0.1%
---------------	--	-------	-------	-------

WORKING DISTANCE	OPTICAL MAGNIFICATION	FIELD OF VIEW	
		H	V
1000	0.0355X	203.4342	152.5756
900	0.0374X	193.1501	137.1493
850	0.0418X	172.5808	129.4356
800	0.0445X	162.2953	121.7215
750	0.0475X	152.0092	114.0069
700	0.0509X	141.7223	106.2917
650	0.0549X	131.4345	98.5759
600	0.0596X	121.1456	90.8592
550	0.0651X	110.8553	83.1415
500	0.0717X	100.5632	75.4224
450	0.0799X	90.2690	67.7018
400	0.0902X	79.9719	59.9789
350	0.1036X	69.6710	52.2533
300	0.1216X	59.3650	44.5237
250	0.1472X	49.0516	36.7887
200	0.1866X	38.7274	28.5456

外观标准	60--40
WORKING TEMPERATURE	-20℃~60℃
STORAGE TEMPERATURE	-20℃~60℃

Common Tolerance		④				Material:	
		③					
Angle	±0.5°	②				3RD_ANGLE_PROJN	
		①					
0.000	±0.01	Rev	Description		Name	Date	Model:
0.00	±0.03	Design	Examine	Checked	Approved		
0.0	±0.05						Part Name:
0	±0.1						

Material:		
/		
3RD_ANGLE_PROJ		Model:
		35MM-C MOUNT
Unit	mm	Part Name:
Scale	2:1	
Ver	00	Dwg No:
Date	2023. 09. 24	
		FA3501A-SPEC-V1

