




Main Specification			
Magnification	-0.7	-0.75	-0.85
Working Distance	304.5±5	285.5±5	267.5±5
Image Distance	196.7±2.5	204±2.5	218.7±2.5
Conjugate Distance	581.2±9	574.5±9	566.1±9
Flange Focal Distance			
Max image	ø82		
F/#	4.0		
EFL	146		
FOV	18.1°		
ENP Diameter	36.7		
Distortion	0.002%		
Structure	8G		
IMAGE QUALITY			
AXIS	ø46.2	ø66	ø82
200lp/mm	160lp/mm	160lp/mm	125lp/mm

倍率 (β)	共轭距 (I/O)	工作距 (WD)	镜头长度 (L)	Φ43.27 视场	Φ57 视场	Φ80 视场
0.70x	581.2	304.5	270	61.8	81.4	114.3
0.72x	578	293.5	273	60.1	79.2	111.1
0.75x	574.5	285.5	277	57.7	76.0	106.7
0.78x	571.4	283.5	281	55.5	73.1	102.6
0.8x	569	279	284	54.1	71.3	100.0
0.82x	568	274.5	287	52.8	69.5	97.6
0.85x	566.1	267.5	292	50.9	67.1	94.1
TOLERANCE: LINEARITY TOLERANCES ±0.05 ANGULAR TOLERANCES ARE±30' DRAFT ANGLES AREA±0.5°/SIDE				三角法	材料(环保)	单位 比例
						mm 1:1
设计				CHKP	2024-03-20	名称
校对						LS1607A规格书
审核						代号
批准						LS1607A-0.75X-M72-SPEC
标记	处数	更改文件号	担当	变更日期	批准	版本
						V2